Z5624 Page 1 of 2

Instructions Rear Swaybar Kit

N.B: This instruction sheet should be used in conjunction with the workshop manual and proper safety procedures followed.

Kit Contents:

1x Swaybar 2x U-bolts 2x Flat plates 2x Angled plates 2x Saddles 2x D bushings 2x Threaded Links 2x Bolts 8x Cupped washers 8x Flange nuts 6x Nyloc nuts 2x Flat washers 8x Link bushings

Application: Ford Falcon XK to XC - Suits cars without OE swaybar

Refer catalogue for vehicles with or without 9 inch diff

1. Raise vehicle evenly and safely support.

2. Position D bushings on swaybar, then proceed to hang Swaybar under differential as per image 1.
- using supplied U bolts/flange nuts, flat plate, and saddle. Careful of brake lines.

3. Bolt up supplied links to the swaybar (with angled plates) as per image 2. Face washers away from bushings - refer image 4.

Proceed to swing bar up towards chassis rail.

Image 1



Image 2



N.B: It is recommended that a licenced workshop or tradesperson carry out the above procedure and that workshop manual and relevant safety procedures are followed in addition to the above.

Z5624 Page 2 of 2

Instructions Rear Swaybar Kit

N.B: This instruction sheet should be used in conjunction with the workshop manual and proper safety procedures followed.

Kit Contents:

1x Swaybar 2x U-bolts 2x Flat plates 2x Angled plates 2x Saddles 2x D bushings 2x Threaded Links 2x Bolts 8x Cupped washers 8x Flange nuts 6x Nyloc nuts 2x Flat washers 8x Link bushings

Application:

Ford Falcon XK to XC - Suits cars without OE swaybar

Refer catalogue for vehicles with or without 9 inch diff

NOTE: If vehicle equipped with OE Tramp Rods, drill plate to 12mm, remove nut - fix plate to Tramp Rod bolt.

4. Mark holes on chassis rail, then remove plate and drill.

Bolt up plate with supplied bolt, flat washers and nyloc nut.

5. Tighten all nuts, ensuring swaybar is central - do not over tighten link nuts.

Image 4



Image 3



Z5326

GREASE FREE TECHNOLOGY

Introducing Grease Free Technology Bushings

Bushings supplied in this kit feature not only the latest synthetic elastomer bushing material technology but a high performing PTFE inner lining boasting an extraordinary low coefficient of friction. This inner lining eliminates the need to lubricate the bushing on installation and therefore makes these bushing 'grease free'!

Superior friction management

- reduces heat build up known to deform or degrade bushing over time
- dramatically reduces high frequency noises (squeaking)
- eliminates the need for maintenance/ greasing

Installation tip

Ensure a clean mating surface when installing these bushings for optimum performance!

Frequently Asked Questions

What happens if I do apply grease to the lining?

Don't stress, simply wipe away as much of the lubricant from the surface as possible and install. Adding grease does not further improve the bushings function/ performance nor does traces of lubricant impede the function/ performance.

Do I need to grease other areas of the bushing?

Simply, no! Unless the kit is supplied with a grease packet and lubrication instructions, no other area of the bushing requires lubrication.

Do these bushings require maintenance?

Significant improvements in grease retention within bushing design has dramatically improved over recent years, however this new grease free technology does away with all lubricants and subsequent or periodical maintenance.

Is this technology available across the entire range?

For the most up to date offering of grease free technology bushings visit the website!



PTFE LINING





FRICTION FREE I SILENT OPERATION I MAINTENANCE FREE

Copyright Australia - ABN - 99 124 177 297